

Ferrule K Talurit®



Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for single layer steel wire ropes with round strands up to fill factor 0,60 and grade 1960.

Material: Aluminum

Marking: According to standard

Standard: Talurit splicing system

The ferrules do not correspond to standard EN 13411-3 but have been tested and verified by Talurit.

Note: See the manufacturer's product data sheet below for guidance on dimension selection.

| Part Code | Ferrule size mm mm | Length mm |
|--------------|--------------------------|--------------|
| 120100900030 | 9 | 36 |
| 120101000030 | 10 | 41 |
| 120101100030 | 11 | 45 |
| 120101200030 | 12 | 50 |
| 120101300030 | 13 | 55 |
| 120101400030 | 14 | 59 |
| 120101600030 | 16 | 64 |

| | | |
|--------------|----|-----|
| 120101800030 | 18 | 73 |
| 120102000030 | 20 | 82 |
| 120102200030 | 22 | 91 |
| 120102400030 | 24 | 100 |
| 120102600030 | 26 | 109 |
| 120102800030 | 28 | 118 |
| 120103000030 | 30 | 127 |
| 120103200030 | 32 | 136 |
| 120103400030 | 34 | 146 |
| 120103600030 | 36 | 155 |
| 120103800030 | 38 | 164 |
| 120104000030 | 40 | 173 |
| 120104200030 | 42 | 182 |
| 120104400030 | 44 | 191 |