



## Ferrule K Talurit®

### Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for single layer steel wire ropes with round strands up to fill factor 0,60 and grade 1960.

**Material:** Aluminum

**Marking:** According to standard

**Standard:** Talurit splicing system

*The ferrules do not correspond to standard EN 13411-3 but have been tested and verified by Talurit.*

**Note:** See the manufacturer's product data sheet below for guidance on dimension selection.

<b>Part Code</b>	<b>Ferrule size mm</b>	<b>Length mm</b>	<b>Delivery time</b>
120100900030	9	36	2
120101000030	10	41	2
120101100030	11	45	2
120101200030	12	50	2
120101300030	13	55	2
120101400030	14	59	2
120101600030	16	64	2
120101800030	18	73	2
120102000030	20	82	-
120102200030	22	91	2
120102400030	24	100	2
120102600030	26	109	2
120102800030	28	118	2
120103000030	30	127	2
120103200030	32	136	-
120103400030	34	146	2
120103600030	36	155	-
120103800030	38	164	-
120104000030	40	173	-
120104200030	42	182	-
120104400030	44	191	-