



Round Sling EXTREEMA® XS

Product information

The XS round slings are the ultimate solution for lifting loads ranging from 1T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m

Material: HMPE -Dyneema®

Marking: According to standard, CE-marked

Temperature range: -50°C up to +70°C

Standard: EN 1492-2

except material

Safety factor: 7:1

| Part code | WLL ton |
|-----------------|------------|
| 340500300050030 | 3 |
| 340500300080030 | 3 |
| 340500300100030 | 3 |
| 340500300150030 | 3 |
| 340500300200030 | 3 |
| 340500300250030 | 3 |
| 340500300300030 | 3 |
| 340500300400030 | 3 |
| 340500300500030 | 3 |
| 340500500050030 | 5 |
| 340500500100030 | 5 |
| 340500500150030 | 5 |
| 340500500200030 | 5 |
| 340500500250030 | 5 |
| 340500500300030 | 5 |
| 340500500400030 | 5 |
| 340500500500030 | 5 |
| 340500500600030 | 5 |
| 340501000150030 | 10 |
| 340501000200030 | 10 |
| 340501000300030 | 10 |
| 340501000400030 | 10 |

Technical data

| Extreema® XS roundsling | | | | |
|-------------------------|----|-----------|------------------|--------------|
| HMPE EXS | | | | |
| WLL | SF | Core ø mm | Weight kg 3m EWL | p/m extra kg |
| 3t | 7 | 9 | 0,8 | 0,25 |
| 5t | 7 | 14 | 1,35 | 0,43 |
| 10t | 7 | 23 | 2 | 0,65 |
| 15t | 7 | 31 | 3,5 | 1,15 |
| 20t | 7 | 37 | 4,6 | 1,50 |