

Steel wire rope veropro 10

Product information



Wire rope construction: veropro 10 is a very flexible 10-strand, non-rotation resistant rope with compacted strands and a rope core covered with a plastic layer.

Features:

- Very high breaking strength
- Very stable rope structure and achieves excellent bending fatigue results
- Offers excellent resistance to crushing and abrasion
- Perfect spooling behavior on multilayer drum.

ISO 4309 Rope Category No: All Diameters **RCN.11.**

Marking: According to standard

Standard: EN 12385-4


Note: veropro 10 may not be used with a swivel.

Fill factor: 0.683

RCN: 11

Tolerance Ø: +2% to +4%

Overhead cranes



Mobile port crane



Offshore crane



Loading crane



Crawler crane



Container crane



Tower crane



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m
103106204300309	62	2,160	-	-	Galvanized	-
103103005070309	30	1,960	-	-	Bright	-
103103205070309	32	1,960	-	-	Bright	-
103103405070309	34	1,960	-	-	Bright	-
103103605070309	36	1,960	-	-	Bright	-
103103805070309	38	1,960	-	-	Bright	-
103104005070309	40	1,960	-	-	Bright	-
103104205070309	42	1,960	-	-	Bright	-
103104405070309	44	1,960	-	-	Bright	-
103104605070309	46	1,960	-	-	Bright	-
103104805070309	48	1,960	-	-	Bright	-
103105005070309	50	1,960	-	-	Bright	-
103105205070309	52	1,960	-	-	Bright	-
103105404070309	54	1,960	-	-	Bright	-
103105605070309	56	1,960	-	-	Bright	-
103105805070309	58	1,960	-	-	Bright	-
103106005070309	60	1,960	-	-	Bright	-
103106405070309	64	1,960	-	-	Bright	-
103106605070309	66	1,960	-	-	Bright	-
103106805070309	68	1,960	-	-	Bright	-
103107005070309	70	1,960	-	-	Bright	-