

Steel Wire Rope verotop E

Product information



Wire rope construction: verotop E is a flexible rotation-resistant rope with compacted outer strands.

Properties:

- High breaking strength with very strong resistance to drum crushing.
- Very good bending fatigue results..
- Great resistance to crushing and abrasion.

ISO 4309 Rope Category No: All Diameters **RCN.23-2.**

Marking: According to standard

Standard: EN 12385-4

Note: verotop E can be used either with or without a swivel.

Fill factor: 0.7

RCN: 23-2

Tolerance Ø: +2% to +4%


Tower crane



Truck crane



Overhead cranes



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m
104100805070139	8	1,960	-	-	Bright	-
104100905070139	9	1,960	-	-	Bright	-
104101005070139	10	1,960	-	-	Bright	-
104101105070139	11	1,960	-	-	Bright	-

104101205070139	12	1,960	-	-	Bright	-
104101305070139	13	1,960	-	-	Bright	-
104101405070139	14	1,960	-	-	Bright	-
104101505070139	15	1,960	-	-	Bright	-
104101605070139	16	1,960	-	-	Bright	-
104101805070139	18	1,960	-	-	Bright	-
104101905070139	19	1,960	-	-	Bright	-
104102005070139	20	1,960	-	-	Bright	-
104102205070139	22	1,960	-	-	Bright	-
104102305070139	23	1,960	-	-	Bright	-
104102405070139	24	1,960	-	-	Bright	-
104102505070139	25	1,960	-	-	Bright	-
104102605070139	26	1,960	-	-	Bright	-
104102705070139	27	1,960	-	-	Bright	-
104102805070139	28	1,960	-	-	Bright	-
104102905070139	29	1,960	-	-	Bright	-
104103005070139	30	1,960	-	-	Bright	-
104103205070139	32	1,960	-	-	Bright	-
104103405070139	34	1,960	-	-	Bright	-
104103505070139	35	1,960	-	-	Bright	-
104103605070139	36	1,960	-	-	Bright	-
104103805070139	38	1,960	-	-	Bright	-
104104005070139	40	1,960	-	-	Bright	-

Technical data