



Offshore crane



Steel Wire Rope verotop XP

Product information



Wire rope construction: verotop XP is a rotary swaged rotation-resistant rope with compacted strands and a rope core covered with a plastic layer.

Features:

- The strongest of all rotation-resistant ropes.
- Very stable rope structure and achieves good bending fatigue results.
- It also avoids internal wear and protects the core in corrosive environments.
- Offers superior crushing resistance and best resistance to abrasion.
- Possesses perfect spooling behavior on multilayer drum.

ISO 4309 Rope Category No: All Diameters **RCN.23-1**

Marking: According to standard

Standard: EN 12385-4

Note: verotop XP can be used either with or without swivel.

Fill factor: 0.745

RCN: 23-1

Tolerance Ø: +2% to +4%

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m
104101205070169	12	1,960	-	-	Bright	-
104101275070169	12.7	1,960	-	-	Bright	-
104101305070169	13	1,960	-	-	Bright	-

104101405070169	14	1,960	-	-	Bright	-
104101505070169	15	1,960	-	-	Bright	-
104101605070169	16	1,960	-	-	Bright	-
104101705070169	17	1,960	-	-	Bright	-
104101805070169	18	1,960	-	-	Bright	-
104101905070169	19	1,960	-	-	Bright	-
104102005070169	20	1,960	-	-	Bright	-
104102105070169	21	1,960	-	-	Bright	-
104102205070169	22	1,960	-	-	Bright	-
104102245070169	22.4	1,960	-	-	Bright	-
104102305070169	23	1,960	-	-	Bright	-
104102405070169	24	1,960	-	-	Bright	-
104102505070169	25	1,960	-	-	Bright	-
104102544270169	25.4	1,960	-	-	Galvanized	-
104102604270169	26	1,960	-	-	Galvanized	-
104102704270169	27	1,960	-	-	Galvanized	-
104102804270169	28	1,960	-	-	Galvanized	-
104102864270169	28.6	1,960	-	-	Galvanized	-
104102904270169	29	1,960	-	-	Galvanized	-
104103004270169	30	1,960	-	-	Galvanized	-
104103104270169	31	1,960	-	-	Galvanized	-
104103204270169	32	1,960	-	-	Galvanized	-
104103304270169	33	1,960	-	-	Galvanized	-

104103404270169	34	1,960	-	-	Galvanized	-
104103504270169	35	1,960	-	-	Galvanized	-
104103604270169	36	1,960	-	-	Galvanized	-
104103804270169	38	1,960	-	-	Galvanized	-
104104004270169	40	1,960	-	-	Galvanized	-
104104134270169	41.3	1,960	-	-	Galvanized	-
104104204270169	42	1,960	-	-	Galvanized	-
104104404270169	44	1,960	-	-	Galvanized	-
104104504270169	45	1,960	-	-	Galvanized	-
104104604270169	46	1,960	-	-	Galvanized	-
104104754270169	47.5	1,960	-	-	Galvanized	-
104104804270169	48	1,960	-	-	Galvanized	-

Technical data