

Hoist rope 8 x 19

Product information



General: Elstar 8SF, 8 Strand Fibre Core Hoist Rope

Post Formed & Preformed.


Features: Good Flexibility & Fatigue Properties. Lubricated with T55 in Manufacture.

Marking: According to standard

Finish: Ungalvanised

Standard: EN 12385-5

Elevator



| Part Code | Rope Diameter, | Tensile strength N/mm ² | Finish | Rope lay. | Min. Breaking force, kN | Steel area mm ² | Lubrication | Weight kg/100m |
|-----------------|----------------|---------------------------------------|--------|-----------|----------------------------|-------------------------------|------------------|-------------------|
| 106100804020179 | 8 | 1,570 | Bright | sZ | 29.4 | 22.8 | SupplierStandard | 21.8 |
| 106100904020179 | 9 | 1,570 | Bright | sZ | 37.3 | 28.6 | SupplierStandard | 27.5 |
| 106100954020179 | 9.5 | 1,570 | Bright | sZ | 41.5 | 31.8 | SupplierStandard | 30.7 |
| 106101004020179 | 10 | 1,570 | Bright | sZ | 46 | 34.5 | SupplierStandard | 34 |
| 106101104020179 | 11 | 1,570 | Bright | sZ | 55.7 | 42.4 | SupplierStandard | 41.1 |
| 106101204020179 | 12 | 1,570 | Bright | sZ | 66.2 | 51.2 | SupplierStandard | 49 |
| 106101304020179 | 13 | 1,570 | Bright | sZ | 77.7 | 59.8 | SupplierStandard | 57.5 |
| 106101604020179 | 16 | 1,570 | Bright | sZ | 118 | 89.5 | SupplierStandard | 87 |