

## Extra strengthened Round sling

### Product information



Round sling – Extra Strengthened

Extra-reinforced sleeve for a better resistance to tear and wear, abrasion, puncture.

Sleeve constituted of woven strands with extra thickness (relief patterns) for more resistance. Configuration: Endless sling including a bearing fiber core in textile wire totally protected in a woven sleeve

**Material:** Fiber core and sleeve : 100% polyester high tenacity multifilament fibers.

**Marking:** According to standard, Manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

**Temperature range:** From -40°C to +100°C

**Finish:** High resisting blue pvc label sewn on the sling.

**Standard:** EN 1492-2

**Note:** Instructions of use : Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings.

**Safety factor:** 7:1

**Part Code**

**WLL  
ton**

340100100100190

1

340100100150190

1

340100100200190

1

340100100250190

1

340100100300190

1

340100100400190

1

340100100500190

1

340100100600190	1
340100100700190	1
340100100800190	1
340100100900190	1
340100101000190	1
340100200100190	2
340100200150190	2
340100200200190	2
340100200250190	2
340100200300190	2
340100200400190	2
340100200500190	2
340100200600190	2
340100200700190	2
340100200800190	2
340100200900190	2
340100201000190	2
340100300100190	3
340100300150190	3
340100300200190	3
340100300250190	3
340100300300190	3
340100300400190	3

340100300500190	3
340100300600190	3
340100300700190	3
340100300800190	3
340100300900190	3
340100301000190	3
340100400100190	4
340100400150190	4
340100400200190	4
340100400250190	4
340100400300190	4
340100400400190	4
340100400500190	4
340100400600190	4
340100400700190	4
340100400800190	4
340100400900190	4
340100401000190	4
340100500100190	5
340100500150190	5
340100500200190	5
340100500250190	5
340100500300190	5

340100500400190	5
340100500500190	5
340100500600190	5
340100500700190	5
340100500800190	5
340100500900190	5
340100501000190	5
340100600100190	6
340100600150190	6
340100600200190	6
340100600250190	6
340100600300190	6
340100600400190	6
340100600500190	6
340100600600190	6
340100600700190	6
340100600800190	6
340100600900190	6
340100601000190	6
340100800100190	8
340100800150190	8
340100800200190	8
340100800250190	8

340100800300190	8
340100800400190	8
340100800500190	8
340100800600190	8
340100800700190	8
340100800800190	8
340100800900190	8
340100801000190	8
340101000100190	10
340101000150190	10
340101000200190	10
340101000250190	10
340101000300190	10
340101000400190	10
340101000500190	10
340101000600190	10
340101000700190	10
340101000800190	10
340101000900190	10
340101001000190	10

## Blueprint

