



## WIMAG Pipe Suspension Grab

### Product information

Indispensable pipe suspension grab for transport and pipe laying.  
Reliable, no accidents, no damages.  
Contact surface of clamp is steel/serrated.

- Gripping depth extended from 220 mm to 260 mm.
- Clamping range 90-200 mm (with rubber coating 50-150 mm).
- Simple and fast adjustment of the clamping range via threaded spindle.
- Gripping surfaces are grooved to prevent load slip.
- Rubber-lined clamps on request.
- Type 200D for prefabricated manholes according to DIN 4032 Part 1 with socket end for axial seal.
- Can also be used acc. to DIN 4032 Part 2.
- Other Wimag types according to DIN 4032 Part 2.
- Can be delivered with longer chains.

**Material:** Clamp made of hollow sections, therefore torsion resistant and very light. Highstrength chains DIN 5687-5.

Part Code	Code	WLL ton	Jaw width mm	Number of clamps	Manhole inside dia. m	Chain length m	Weight kg
655600150000020	RSV 1,5	1.5	40-120	3	0,4-2,0	1,5	31
655600300000020	RSV 3/230	3	90-230	3	0,4-2,0	1,6	54
655600300000020	RSV 3	3	50-180	3	0,4-2,0	1,6	55
655600300000020	RSVL 3/230	3	90-230	3	0,4-3,0	2,2	58
655600300000020	RSV 3/200 D	3	90-200	3	0,4-2,0	1,6	69
655600300000020	RSVL 3/200 D	3	90-200	3	0,4-3,0	2,2	73