



## SS 6x36 IWRC

### Product information

*sZ zS SS*

Stainless steel wire rope.

**Design:** Cross lay right-handed, alternative design on request.

**Rope construction:** 6x36 IWRC.

**Material:** AISI 316/1570 N/mm<sup>2</sup>

Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Min. Breaking force kN.	Finish	Weight kg/100m
108100804620178	8	1,570	36.6	Stainless	27
108100803620178	8	1,570	36.6	Stainless	27
108101004620178	10	1,570	56.9	Stainless	42
108101003620178	10	1,570	56.9	Stainless	42
108101204620178	12	1,570	80.6	Stainless	60.2
108101203620178	12	1,570	80.6	Stainless	60.2
108101304620178	13	1,570	94.8	Stainless	70.7
108101303620178	13	1,570	94.8	Stainless	70.7
108101404620178	14	1,570	109	Stainless	82
108101403620178	14	1,570	109	Stainless	82
108101504620178	15	1,570	125.8	Stainless	94.5
108101503620178	15	1,570	125.8	Stainless	94.5
108101604620178	16	1,570	142	Stainless	107
108101603620178	16	1,570	142	Stainless	107
108101804620178	18	1,570	180	Stainless	135
108101803620178	18	1,570	180	Stainless	135
108102004620178	20	1,570	221	Stainless	167
108102003620178	20	1,570	221	Stainless	167
108102404620178	24	1,570	321	Stainless	241
108102403620178	24	1,570	321	Stainless	241