



Wire Rope Sling - Two Leg

Product information

- Galvanized steel wire rope
- Alloy steel hook and masterlink
- On request hook with safety latch or self-locking hook
- The working load limit (WLL) is calculated according to EN 13414-1 / A1. It can be modified according to the class of resistance of the wire rope used (1770 or 1960 MPa).

Marking: According to standard

Standard: EN 13414-1

Safety factor: 5:1

Part Code	Rope Diameter, mm	Masterlink	WLL 45-60° ton	WLL 0-45° ton	Hook opening mm
1605	7	100 X 60	0.5	0.7	22.6
1605	8	100 X 60	0.65	0.9	22.6
1605	10	100 X 60	1	1.4	22.6
1605	12	100 X 60	1.4	2	23.1
1605	14	120 X 70	2.12	3	27.7
1605	16	135 X 75	2.7	3.7	27.7
1605	18	135 X 75	3.4	4.7	34.5
1605	20	150 X 90	4.35	6	34.5
1605	22	150 X 90	5.2	7.2	40.9
1605	24	170 X 95	6.3	8.8	40.9
1605	26	170 X 95	7.2	10	40.9
1605	29	200 X 120	9	12.5	52.8
1605	32	200 X 120	11	15	52.8
1605	34	250 X 150	13.5	19	57.7
1605	36	250 X 150	15	21	57.7
1605	38	250 X 150	17	23.5	76.7
1605	40	250 X 150	19	26.5	76.7