



## Master Link Assembly

### Product information

Can be use with chains and wire ropes.

For 3 or 4 legs slings

**Material:** Alloy steel

**Marking:** According to standard

**Finish:** Painted

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 8

Part Code	WLL ton	Chain 3 and 4 legs	A mm	B mm	Ø D mm	a mm	b mm	Ø d	Weight kg	Delivery time
401100270240	2.7	6	120	70	16	100	60	13	1.2	2
401100350240	3.5	7	135	75	18	100	60	16	1.8	2
401100800240	8	8/10	150	90	22	120	70	18	2.9	-
401100900240	9	-	170	95	25	120	70	20	3.9	-
401101120240	11.2	13	200	120	28	120	70	20	4.9	-
401101300240	13	-	200	120	30	135	75	22	6	-
401101760240	17.6	16	250	150	36	135	75	25	9.6	-
401102000240	20	-	250	150	38	170	95	28	12.6	-
401102700240	27	18/20	280	170	45	200	120	33	19.7	-
401103200240	32	22	300	200	45	200	120	36	22.5	-
401104000240	40	32	300	200	50	150	90	38	24.5	-
401105000240	50	26	300	200	55	150	90	38	28	-
401106000240	60		350	200	58	150	90	42	34.6	-
401108000240	80	32	400	250	70	300	150	55	74.7	-
401110000240	100	-	400	250	80	300	150	58	92.4	-

# Blueprint

