

Weld-on Swivel Hoist Ring Codipro WE DSS



Product information

- Weld-on swivel hoist ring.
- 360° rotation.
- Swivelling under load.
- 180° articulation.
- Control anti-crack on 100% of the product.
- Fatigue test.

Marking: According to standard, CE-marked

Temperature range: -20°C up to + 200°C

Standard: EN 1677-1

Safety factor: 5:1


Part Code	WLL ton	A mm	a mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
4215WEDSS10	10	74	7	44	70	104	73	149	33	5.5

Technical data

5:1

METRIC THREADS

max. load in t



	1	2	1	2	2	2	Asymmetric	3 → 4	3 → 4	Asymmetric
Number of rings	1	2	1	2	2	2	Asymmetric	3 → 4	3 → 4	Asymmetric
Lifting angle β	0°	0°	0°	0°	0° → 45°	45° → 60°	Asymmetric	0° → 45°	45° → 60°	Asymmetric
Loading angle α	0°	0°	90°	90°	0° → 45°	45° → 60°		0° → 45°	45° → 60°	
WE.DSR 2	2,00	4,00	2,00	4,00	2,80	2,00	2,00	4,20	3,00	2,00
WE.DSR 5	5,00	10,00	5,00	10,00	7,00	5,00	5,00	10,50	7,50	5,00
WE.DSS 10	10,00	20,00	10,00	20,00	14,00	10,00	10,00	21,00	15,00	10,00

Blueprint

