

## Lifting Eye Nut DIN 582 Stainless steel



### Product information

Stainless steel lifting eye.

Different angles of inclination.

**Material:** AISI 316

**Marking:** CE-marked, WLL, material, supplier name, lifting angle, tracking lot number

**Finish:** Polished

**Safety factor:** 6:1

| Part Code    | WLL ton | Thread mm | WLL 90° ton | WLL 0-45° ton | A mm | B mm | C mm | D mm | E mm | S mm | Weight kg |
|--------------|---------|-----------|-------------|---------------|------|------|------|------|------|------|-----------|
| 421100010392 | 0.09    | M6        | 0.045       | 0.06          | 6    | 36   | 20   | 20   | 8.5  | 8    | 0.06      |
| 421100140390 | 0.14    | M8        | 0.07        | 0.1           | 8    | 36   | 20   | 20   | 8.5  | 8    | 0.05      |
| 421100230390 | 0.23    | M10       | 0.115       | 0.17          | 10   | 45   | 25   | 25   | 10   | 10   | 0.1       |
| 421100340390 | 0.34    | M12       | 0.17        | 0.24          | 12   | 54   | 30   | 30   | 11   | 12   | 0.16      |
| 421100050390 | 0.5     | M14       | 0.25        | 0.35          | 14   | 54   | 30   | 30   | 11   | 12   | 0.16      |
| 421100070390 | 0.7     | M16       | 0.35        | 0.5           | 16   | 63   | 35   | 35   | 13   | 14   | 0.24      |
| 421100120390 | 1.2     | M20       | 0.6         | 0.86          | 20   | 72   | 40   | 40   | 16   | 16   | 0.38      |
| 421100180390 | 1.8     | M24       | 0.9         | 1.29          | 24   | 90   | 50   | 50   | 20   | 20   | 0.77      |
| 421100320390 | 3.2     | M30       | 1.6         | 2.3           | 30   | 108  | 60   | 65   | 25   | 24   | 1.6       |

## Blueprint

