

Aluminium Jack

Product information



- Capacity from 6,5 to 100 tons; Strokes from 75 to 300 mm.
- Equipped with an overload protection valve.
- Easy to use, models from 20 to 100 tons can be operated vertically or with front face in horizontal position.

Material: Aluminium

Marking: CE-marked

| Part Code | WLL ton | Height mm | Stroke mm | Overall height mm | Weight kg |
|-----------|---------|-----------|-----------|-------------------|-----------|
| 5205 | 6.5 | 131 | 75 | 131 | 3.6 |
| 5205 | 10 | 182 | 115 | 182 | 6.3 |
| 5205 | 20 | 265 | 152 | 265 | 10.9 |
| 5205 | 30 | 265 | 152 | 265 | 15.4 |
| 5205 | 60 | 500 | 305 | 500 | 43.7 |
| 5205 | 100 | 315 | 152 | 315 | 49 |

Technical data

| Code | Jack with lifting claw | Jack with safety lock nut | | | |
|---------------------|------------------------|--------------------------------------|---------------------|-------------|------|
| Overall height (mm) | Weight (Kg) | Capacity of lifting claw max. (tons) | Overall height (mm) | Weight (Kg) | |
| AJS-65 | - | - | - | - | - |
| AJS-104 | - | - | - | - | - |
| AJS-620 | 280 | 14,5 | 8 | 291 | 10,9 |
| AJS-630 | 284 | 20,3 | 12 | 294 | 15,4 |
| AJS-1260 | 533 | 64,9 | 24 | 536 | 43,7 |
| AJS-6100 | - | - | | | |