

Aluminium Hollow Plunger Cylinder HAHC S

Product information



Holmatro aluminium hollow plunger cylinders (HAHC) - Spring or hydraulic return

Unique specifications:

- Up to 60% lighter compared to steel cylinders - easy & ergonomic
- Compact design and a lower build-in
- Suitable for pulling, lifting, tensioning in all positions
- Duo power ring; a combination of a superior seal and an extremely strong composite bearing for a longer life span
- The plunger is coated with a hardened anodized layer, which makes it extremely wear & corrosion resistant

Standard supplied with:

- High flow female coupler A118
- Hollow saddle; prevents damage to the plunger
- Larger cylinders are equipped with foldable handles for easy carrying and positioning

Also available:

- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

Material: Aluminium

Part Code	Code	WLL ton	stroke length mm	Closed height mm	required oil cc	Weight kg
5211100112366	HAHC20S5	20	50	170	144	3.4
5211100112367	HAHC20S10	20	100	240	288	4.3
5211100112368	HAHC20S15	20	150	310	433	5.5
5211100112369	HAHC20S20	20	200	375	577	6.3
5211100112370	HAHC20S25	20	250	429	721	7.1
5211100112371	HAHC30S5	30	50	185	238	6.1
5211100112372	HAHC30S10	30	100	255	477	7.8
5211100112373	HAHC30S15	30	150	325	715	9.5
5211100112374	HAHC30S20	30	200	390	954	11.1
5211100112375	HAHC30S25	30	250	450	1,192	12.6
5211100112376	HAHC60S5	60	50	243	421	15.5
5211100112377	HAHC60S10	60	100	295	842	18.6
5211100112378	HAHC60S15	60	150	363	1,263	21.8
5211100112379	HAHC60S20	60	200	428	1,684	25.4
5211100112380	HAHC60S25	60	250	518	2,105	29

Blueprint

