



Eye Nut 802

Product information

Eye nut to be screwed by hand.

Material: Alloy steel 8.8.

Marking: Marked with WLL, sizes, steel quality, CE, producername, tracability.

Finish: Red painted.

Note: Approved for lifting.

Safety factor: 4:1

| Part Code | WLL ton | Thread mm | A mm | B mm | C mm | E mm | F mm | H mm | Weight kg |
|--------------|---------|-----------|------|------|------|------|------|------|-----------|
| 421100040120 | 0.4 | M6 | 25 | 45 | 25 | 10 | 10 | 45 | 0.1 |
| 421100080120 | 0.8 | M8 | 25 | 45 | 25 | 10 | 10 | 45 | 0.1 |
| 421100100120 | 1 | M10 | 25 | 45 | 25 | 10 | 10 | 45 | 0.1 |
| 421100160120 | 1.6 | M12 | 35 | 63 | 35 | 14 | 14 | 62 | 0.26 |
| 421100300120 | 3 | M14 | 35 | 63 | 35 | 14 | 14 | 62 | 0.26 |
| 421100400120 | 4 | M16 | 35 | 63 | 35 | 14 | 14 | 62 | 0.26 |
| 421100500120 | 5 | M18 | 50 | 90 | 50 | 20 | 20 | 90 | 0.75 |
| 421100600120 | 6 | M20 | 50 | 90 | 50 | 20 | 20 | 90 | 0.75 |
| 421100800120 | 8 | M24 | 50 | 90 | 50 | 20 | 20 | 90 | 0.75 |
| 421101000120 | 10 | M27 | 60 | 108 | 65 | 24 | 24 | 109 | 1.4 |
| 421101200120 | 12 | M30 | 60 | 108 | 65 | 24 | 24 | 109 | 1.4 |

Technical data

| | □ | □ | □ | | □ | |
|------|------------|-------|--------|---------|-------------|---------|
| | 0° | 0° | 0°-45° | 45°-60° | 0°-45° | 45°-60° |
| | WLL tons | | | | | |
| Size | Single-leg | 2-leg | 2-leg | | 3- or 4-leg | |
| M6 | 0,4 | 0,8 | 0,14 | 0,1 | 0,2 | 0,14 |
| M8 | 0,8 | 1,6 | 0,28 | 0,2 | 0,4 | 0,28 |
| M10 | 1,0 | 2,0 | 0,35 | 0,25 | 0,5 | 0,35 |
| M12 | 1,6 | 3,2 | 0,56 | 0,4 | 0,8 | 0,56 |
| M14 | 3,0 | 6,0 | 1,0 | 0,75 | 1,5 | 1,0 |
| M16 | 4,0 | 8,0 | 1,4 | 1,0 | 2,0 | 1,4 |
| M18 | 5,0 | 10 | 1,8 | 1,25 | 2,5 | 1,8 |
| M20 | 6,0 | 12 | 2,1 | 1,5 | 3,0 | 2,1 |
| M24 | 8,0 | 16 | 2,8 | 2,0 | 4,0 | 2,8 |
| M27 | 10 | 20 | 3,5 | 2,5 | 5,0 | 3,5 |
| M30 | 12 | 24 | 4,2 | 3,0 | 6,0 | 4,2 |

Blueprint

