

Hand spurgear winch MANIBOX GR, Painted

Product information



Hand spurgear winches from 300 to 2750 kg for daily use.

Applications:

- Industry
- Auditoriums, theatre scenery
- Water treatment, water dams
- Sports rooms
- Hanging chandeliers

Technical properties:

- Compact and rugged construction with steel frame.
- Machined parts.
- Steel or cast iron drum depending on models.
- Flat mounted or wall mounted positions for GR 300/530/500.
- 4 fixation points.
- Fully protected gear system.
- Removable crank positioned on the left hand side for the GR 300/530/500/750 and on the right hand side for the GR 1000/1450/2000/2750.
- Free spooling drum, only when not in load.
- Composite material automatic brake. - Failsafe system for correct rope winding direction (patented)

Optional:

Wire rope and hook.

Marking: According to standard, CE-marked

Temperature range: -10°C up to +50°C

Finish: Painted

Standard: EN 13157

Part Code	WLL ton	Rope Ø mm	Weight without wire rope kg	Capacity 1st layer kg	Number of layers	Lift per crank revolution mm	Max. crank effort kg	Max. drum capacity m	Drum Ø mm	A	B	C	D	E	F	G	K	Lg	S	T
501300030000140	0.3	5	15	500	6	30.5	12.6	38	62	249	400	190	217	240	200	145	144	122	184	76
501300050000140	0.5	7	15	750	4	31.5	12.5	18	62	249	400	190	217	240	200	145	144	122	184	76
501300530000140	0.53	6	15	530	1	30.5	12.5	4	62	249	400	190	217	240	200	145	144	122	184	76
501300750000140	0.75	7	15	750	1	31.5	19	3	62	249	400	190	217	240	200	-	144	122	-	-
501300100000140	1	9	44	1,450	4	16	14.5	30	103.5	410	485	305	300	340	370	-	236	176	-	-
501300150000140	1.45	10	44	1,450	1	16	14.5	5	103.5	410	485	305	300	340	370	-	236	176	-	-
501300200000140	2	13	83	2,750	3	9.5	16.5	25	121	510	585	360	400	340	440	-	325	237.5	-	-
501300280000140	2.75	13	83	2,750	1	9.5	16.5	6	121	510	585	360	400	340	440	-	325	237.5	-	-

Blueprint

