



Tiger winches

Product information

High quality Tiger winch is suitable for both lifting and pulling. The winch is equipped with an automatic brake function which ensures that there is no risk of load falling or sliding. Brake system and components are encased and protected from dust and rain. Straps and wire ropes are also available separately as spare parts. Steel wire rope or strap need to order separately.

Product equipped with wire rope can be used for lifting and pulling and product with strap only for pulling. Check the ropes and traps from technical data tab.

All the dimension data can be found on the documents tab

Material: Steel

Marking: According to standard

Temperature range: -40°C - (+)80°C

Finish: High quality powder coat, yellow

Standard: EN 13157

| Part Code | WLL ton | Gear ratio | Length handle mm | Wire capacity mtr | Drum diameter mm | Pulling capacity t | Webbing length m | Weight kg |
|-----------------|---------|------------|------------------|-------------------|------------------|--------------------|------------------|-----------|
| 501301850000340 | 0.185 | 4,1:1 | 160 | 36 | 40 | 0.37 | 9.1 | 3 |
| 501302750000340 | 0.275 | 4,1:1 | 210 | 23 | 50 | 0.55 | 8.5 | 3.5 |
| 501300410000340 | 0.41 | 5:01 | 320 | 24 | 70 | 0.82 | 14.1 | 8 |
| 501300060000340 | 0.6 | 10:01 | 320 | 18 | 82 | 1.2 | 10.6 | 10.5 |

Technical data

WIRE ROPES WITH LATCH HOOK (for lifting and pulling)

| For winch t | Length m | Diameter mm | Breaking strength kg |
|--------------|----------|-------------|----------------------|
| 0,185 / 0,37 | 30 | 4 | 1270 |
| 0,275 / 0,55 | 20 | 5 | 2000 |
| 0,41 / 0,82 | 22 | 6 | 3000 |
| 0,6 / 1,2 | 16 | 8 | 4500 |

STRAPS WITH LATCH HOOK (only for pulling)

| For winch t | Length m | Diameter mm | Breaking strength kg |
|--------------|----------|-------------|----------------------|
| 0,185 / 0,37 | 6 | 48 | 2068 |
| 0,275 / 0,55 | 6 | 48 | 2068 |
| 0,41 / 0,82 | 9 | 54 | 2864 |
| 0,6 / 1,2 | 9 | 60 | 4136 |