



## Closed Body Turnbuckles M Series Oval Eye - Oval Eye

### Product information

**General:**

- Standard hot dip galvanized.
- Factory supplied with locking nuts.
- Straight or in-line pull only.
- MBL equals 5x WLL.

Part Code	WLL ton	Take up mm	Thread	MBL ton	L min. mm	L max. mm	A mm	J mm	K mm	L mm	Weight kg
422100030220	0.3	102	M8	1.5	203	305	127	8	9	20	0.3
422100050220	0.5	114	M10	2.5	235	349	152	8	11	25	0.4
422100070220	0.7	200	M12	3.5	330	530	229	11	14	36	0.9
422100120220	1.2	183	M16	6	377	560	229	14	18	40	1.2
422100150220	1.5	155	M20	7.5	410	565	229	17	25	55	2
422100220220	2.2	244	M22	11	486	730	305	17	25	55	3.1
422100320220	3.2	300	M24	16	556	856	356	20	26	57	3.9
422100380220	3.8	280	M27	19	576	856	356	20	26	57	4.8
422100500220	5	280	M33	25	640	920	381	25	34	64	6.8
422100630220	6.3	270	M36	31.5	650	920	381	27	38	75	9
422100700220	7	283	M39	35	687	970	407	27	38	75	10
422100850220	8.5	300	M45	42.5	720	1,020	407	30	40	85	14
422101000220	10	280	M48	50	770	1,050	407	37	44	92	18

# Blueprint

