

## Polypropylene Fibre Rope 3-Strand Staplespun



### Product information

General purpose rope for a variety of marine applications; mooring, towing, fishing, pick-up lines, lifting slings, general purpose use.

**Design:** Spliced fibre.

**Specific gravity:** 0,91 (floats)

**Melting point:** Approx. 165°C

**Elongation:** Approx. 30%.

**Strength wet/dry:** 100%

**Shock Absorption:** Very Good

**Water Absorption:** None

**Abrasion Resistance:** Good

**Standard:** EN ISO 1346:2004

**Material:** Polypropylene, resistant to rot, most acids and alkalis. The fibre is UV-stabilized against sunlight.

**Finish:** White

Part Code	Diameter mm	Minimum Strength Kgf	Weight kg/100m
300300600000120	6	600	1.7
300300800000120	8	1,060	3
300301000000120	10	1,560	4.5
300301200000120	12	2,210	6.5
300301400000120	14	3,050	9
300301600000120	16	3,770	11.5
300301800000120	18	4,810	14.8

30030200000120	20	5,800	18
30030220000120	22	6,950	22
30030240000120	24	8,130	26
30030280000120	28	10,710	35.5
30030320000120	32	13,460	46
30030360000120	36	16,930	58.5
30030400000120	40	20,500	72
30030440000120	44	24,570	88
30030480000120	48	28,550	104
30030520000120	52	33,040	122
30030560000120	56	37,830	142
30030600000120	60	43,240	163
30030640000120	64	48,950	185
30030720000120	72	61,490	234
30030800000120	80	75,560	290