



## Fast Reeve Crane Blocks 2 sheave

### Product information

#### General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

#### Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

#### Important:

**Inquiries for custom versions are welcome!**

Part Code	WLL ton	Model no.	For wire Ø mm	Hooksize	Ø D1 mm	Ø D2 mm	B mm	O mm	TA mm	TB mm	TL mm	L mm	T mm	Ø Z mm	Weight kg
6097FRB22514216E	16	FRB 225 .14 .2 .16 .E	14	6	260	225	608	59	345	180	883	1,103	28	32	105
6097FRB26014216E	16	FRB 260 .14 .2 .16 .E	14	6	300	260	693	59	400	165	978	1,168	28	32	125
6097FRB26016216E	16	FRB 260 .16 .2 .16 .E	16	6	300	260	693	59	400	165	978	1,168	28	32	125

6097FRB26014220E	20	FRB 260 .14 .2 .20 .E	14	8	300	260	748	69	400	165	1,033	1,103	28	32	130
6097FRB26016220E	20	FRB 260 .16 .2 .20 .E	16	8	300	260	748	69	420	165	1,033	1,213	28	32	130
6097FRB28516220E	20	FRB 285 .16 .2 .20 .E	16	8	365	285	778	69	420	165	1,078	1,236	28	32	160
6097FRB32016220E	20	FRB 320 .16 .2 .20 .E	16	8	365	320	768	69	450	180	1,101	1,231	28	32	160
6097FRB32016225E	25	FRB 320 .16 .2 .25 .E	16	8	365	320	763	69	450	230	1,096	1,333	28	32	205
6097FRB35519229E	29	FRB 355 .19 .2 .29 .E	19	8	410	355	848	69	500	225	1,193	1,393	35	37	265
6097FRB40019229E	29	FRB 400 .19 .2 .29 .E	19	8	460	400	873	69	570	240	1,253	1,398	35	37	365
6097FRB40022229E	29	FRB 400 .22 .2 .29 .E	22	8	460	400	873	69	570	240	1,253	1,572	40	43	365
6097FRB45022232E	32	FRB 450 .22 .2 .32 .E	22	10	515	450	1,003	76	600	250	1,416	1,655	40	43	485
6097FRB45022240E	40	FRB 450 .22 .2 .40 .E	22	12	515	450	1,074	84	600	333	1,487	1,665	40	43	590
6097FRB45024240E	40	FRB 450 .24 .2 .40 .E	24	12	515	450	1,074	84	600	333	1,487	1,689	45	52	590
6097FRB45026240E	40	FRB 450 .26 .2 .40 .E	26	12	515	450	1,074	84	600	333	1,497	1,689	45	52	590
6097FRB45024250E	50	FRB 450 .24 .2 .50 .E	22	16	515	450	1,074	97	600	363	1,497	1,675	45	52	680
6097FRB45026250E	50	FRB 450 .26 .2 .50 .E	26	16	515	450	1,074	97	600	363	1,497	1,848	45	52	680
6097FRB52824263E	63	FRB 528 .24 .2 .63 .E	24	16	595	528	1,202	97	710	383	1,656	1,848	45	52	1,000
6097FRB52826263E	63	FRB 528 .26 .2 .63 .E	26	16	595	528	1,202	97	710	383	1,656	1,946	45	52	1,000
6097FRB52828263E	63	FRB 528 .28 .2 .63 .E	28	16	595	528	1,203	97	710	383	1,681	1,971	50	59	1,000
6097FRB52826280E	80	FRB 528 .26 .2 .80 .E	26	20	595	528	1,272	110	710	412	1,736	1,883	45	52	1,065
6097FRB52828280E	80	FRB 528 .28 .2 .80 .E	28	20	595	528	1,273	110	710	412	1,751	2,117	50	59	1,065
6097FRB670282100E	100	FRB 670 .28 .2 .100 .E	28	20	760	670	1,332	110	870	482	1,897	2,122	50	59	2,240
6097FRB670322100E	100	FRB 670 .32 .2 .100 .E	32	20	760	670	1,332	110	870	482	1,897	83,54	60	66	2,240

# Blueprint

