



Standard Reeve Crane Blocks 5 sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

| Part Code | WLL | Model | For wire Ø mm | Hooksize | Weight kg |
|-------------------|-----|------------------------|------------------|----------|--------------|
| 6097SRB35516550E | 50 | SRB 355 .16 .5 .50 .E | 16 | 16 | 500 |
| 6097SRB36019563E | 63 | SRB 360 .19 .5 .63 .E | 19 | 16 | 600 |
| 6097SRB36019580E | 80 | SRB 360 .19 .5 .80 .E | 19 | 20 | 820 |
| 6097SRB40019580E | 80 | SRB 400 .19 .5 .80 .E | 19 | 20 | 835 |
| 6097SRB40022580E | 80 | SRB 400 .22 .5 .80 .E | 22 | 20 | 835 |
| 6097SRB45022580E | 80 | SRB 450 .22 .5 .80 .E | 22 | 20 | 1,025 |
| 6097SRB450245100E | 100 | SRB 450 .24 .5 .100 .E | 24 | 25 | 1,120 |
| 6097SRB450265100E | 100 | SRB 450 .26 .5 .100 .E | 26 | 25 | 1,120 |
| 6097SRB528245125E | 125 | SRB 528 .24 .5 .125 .E | 24 | 32 | 1,820 |
| 6097SRB528265125E | 125 | SRB 528 .26 .5 .125 .E | 26 | 32 | 1,820 |
| 6097SRB528285125E | 125 | SRB 528 .28 .5 .125 .E | 26 | 32 | 1,850 |
| 6097SRB528285160E | 160 | SRB 528 .28 .5 .160 .E | 28 | 40 | 1,820 |
| 6097SRB670285200E | 200 | SRB 670 .28 .5 .200 .E | 28 | 50 | 3,560 |
| 6097SRB670325200E | 200 | SRB 670 .32 .5 .200 .E | 32 | 50 | 3,560 |

Blueprint

