



## Round sling - Double sleeve, middle stitch

### Product information

**General:** Round sling – Double sleeve, middle stitch

This round sling is particularly recommended for the metal frameworks lifting.

The middle stitch gives a better capacity to the fibres that are grouped together to support the effort uniformly.

Flexible endless sling with double sleeve, middle stitch.

Configuration: Endless sling including a bearing fibre core in textile wire totally protected in a double woven sleeve.

Label informations : manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

**Stretch with working Load:** for textile slings

*Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. DO NOT USE DAMAGED SLINGS.*

*Storage : Store in a cool, dry and protected from sunlight area.*

*Maintenance : Never dry sling near a fire or any source of heat*

**Material:** Fibre core and sleeve : 100% polyester high tenacity multifilament fibres.

**Marking:** According to standard, High resisting blue pvc label sewn on the sling.

**Temperature range:** From -40°C to +100°C

**Standard:** EN 1492-2

**Warning:** :

**Safety factor:** 7:1

Part Code	WLL ton
340100100100100	1
340100200100100	2
340100300100100	3
340100400100100	4
340100500100100	5
340100600100100	6
340100800100100	8

## Blueprint

