



## Round sling - Double sleeve side stitch

### Product information

**General:** Round sling – Double sleeve side stitch

The side stitch allows a rounder and therefore more homogeneous sling, particularly adapted to lift heavy loads.

**Design:** High resisting blue pvc label sewn on the sling.

**Stretch with working Load:** for textile slings

**Instructions of use :** *Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. DO NOT USE DAMAGED SLINGS.*

**Storage :** *Store in a cool, dry and protected from sunlight area.*

**Maintenance :** *Never dry sling near a fire or any source of heat.*

**Material:** Fibre core and sleeve : 100% polyester high tenacity multifilament fibres.

**Marking:** According to standard, Manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

**Temperature range:** For textile slings: From -40°C to +100°C.

**Standard:** EN 1492-2

<b>Part Code</b>	<b>WLL ton</b>
340100800100250	8
340101000100250	10
340101500100250	15
340102000100250	20
340102500100250	25
340103000100250	30
340104000100250	40
340105000100250	50
340106000100250	60
340107000100250	70
340108000100250	80
340109000100250	90
340110000100250	100

## Blueprint

