



## Steel Wire Rope ROPETEX S33 Stainless Steel

### Product information

**ROPETEX**



Steel wire rope ROPETEX S33 in stainless steel is a good choice for basic lifting applications in environments where corrosion resistance is important.

ROPETEX S33 is equipped with a Wire Strand Core (WSC) which gives the rope a good strength and a reasonable balance between fatigue and wear resistance.

ROPETEX S33 can be used for applications where the rope runs over sheaves or is spooled on a drum.

#### Typical applications:

- lifting applications
- slings
- winch rope
- stay ropes

**Rope construction:** 6x19M-WSC

**Material:** AISI316 / EN 1.4401

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Standard:** EN 12385-4

*except material*

**Fill factor:** 0,53

General use



Winch rope



Stay rope



Agriculture and livestock



Slings



Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Steel area mm <sup>2</sup>	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
108100204620038	2	1,570	-	-	Stainless	-	-
108100304620038	3	1,570	-	-	Stainless	-	-
108100404620038	4	1,570	-	-	Stainless	-	-
108100504620038	5	1,570	-	-	Stainless	-	-
108100604620038	6	1,570	-	-	Stainless	-	-
108100704620038	7	1,570	-	-	Stainless	-	-
108100804620038	8	1,570	-	-	Stainless	-	-
108101004620038	10	1,570	-	-	Stainless	-	-
108101204620038	12	1,570	-	-	Stainless	-	-
108101404620038	14	1,570	-	-	Stainless	-	-
108101604620038	16	1,570	-	-	Stainless	-	-