

Steel Wire Rope ROPETEX S65 Stainless Steel

Product information

ROPETEX



ROPETEX S65 is a stainless steel rope, the most commonly used range is from 8 to 38 mm. It can be used for cranes, hoists, slings and a wide range of various other applications.

ROPETEX S65 is equipped with an Independent Wire Rope Core (IWRC) which gives it a high breaking strength and dimensionally stability, especially when used on sheaves or drums.

In stainless steel (AISI 316) it's well suited for marine and aggressive environments.

Rope construction: 6x36WS+IWRC

Material: AISI 316 / EN 1.4401

Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: EN 12385-4

except material

Fill factor: 0,59

General use




Winch rope



Stay rope



Overhead cranes



Agriculture and livestock



Slings



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
108101004620048	10	1,570	-	-	Stainless	-	-
108101204620048	12	1,570	-	-	Stainless	-	-
108101404620048	14	1,570	-	-	Stainless	-	-
108101604620048	16	1,570	-	-	Stainless	-	-
108101804620048	18	1,570	-	-	Stainless	-	-
108102004620048	20	1,570	-	-	Stainless	-	-
108102404620048	24	1,570	-	-	Stainless	-	-