

## ROV Shackle D Tapered Pin Green Pin® P-5361D

### Product information



**Certificates:** At no extra charges this product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate and/or EC Declaration of Conformity.

**Material:** Bow and pin alloy steel, Grade 8, quenched and tempered

**Temperature range:** – 40°C up to +200°C

**Finish:** Body white painted, pin green painted

**Safety factor:** MBL equals 5 x WLL

Part Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	Weight kg
420100651310	6.5	22	25	52	22	36	83	58	144	345	102	3.5	3.79
420100951310	9.5	28	32	67	28	47	108	75	185	381	131	5.5	5.38
420101201310	12	32	35	72	32	51	115	83	201	393	147	6.5	6.5
420101701310	17	38	42	88	38	60	146	99	249	417	175	8.5	8.19
420102501310	25	45	50	103	45	74	178	126	300	464	216	8.5	14.2
420103501310	35	50	57	111	50	83	197	138	331	484	238	8.5	19.9
420105501310	55	65	70	145	65	105	260	180	433	545	310	7.5	39.6
-	-	-	-	-	-	-	-	-	-	-	-	-	-

## Blueprint

