

Steel Wire Rope 6x19-WSC stainless

Product information



Steel wire rope 6x19 WSC in stainless steel is a good choice for basic lifting applications in environments where corrosion resistance is important. It is equipped with a Wire Strand Core (WSC) which gives the rope a good strength and a reasonable balance between fatigue and wear resistance. Can be used for applications where the rope runs over sheaves or is spooled on a drum.

Rope construction: 6x19M-WSC

Material: AISI 316

Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: EN 12385-4
except material

Fill factor: 0,53

RCN: 04


Winch rope



Stay rope



Overhead cranes



Agriculture and livestock



Slings



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m
108100204620138	2	1,570	-	-	Stainless	-
108100304620138	3	1,570	-	-	Stainless	-
108100404620138	4	1,570	-	-	Stainless	-
108100504620138	5	1,570	-	-	Stainless	-
108100604620138	6	1,570	-	-	Stainless	-
108100704620138	7	1,570	-	-	Stainless	-
108100804620138	8	1,570	-	-	Stainless	-
108100904620138	9	1,570	-	-	Stainless	-
108101004620138	10	1,570	-	-	Stainless	-
108101104620138	11	1,570	-	-	Stainless	-
108101204620138	12	1,570	-	-	Stainless	-
108101304620138	13	1,570	-	-	Stainless	-
108101404620138	14	1,570	-	-	Stainless	-
108101504620138	15	1,570	-	-	Stainless	-
108101604620138	16	1,570	-	-	Stainless	-
108101804620138	18	1,570	-	-	Stainless	-
108102004620138	20	1,570	-	-	Stainless	-