



S Hook With Safety Latches On Both Sides 1620

Product information

High quality S hook equipped with safety latches on both sides.

Marking: According to standard, CE-marked, Manufacturer sign, WLL, Date of Production MM/YY

Temperature range: -40°C up to +200°C

Standard: DIN EN 683-2

Safety factor: 4:1

Grade: 8

| Part Code | WLL ton | A mm | B mm | C mm | D mm | Weight kg |
|------------------|--------------------|-----------------|-----------------|-----------------|-----------------|----------------------|
| 420500011910 | 0.05 | 6 | 80 | 20 | 15 | 0.06 |
| 420500011911 | 0.1 | 8 | 80 | 20 | 15 | 0.1 |
| 420500021910 | 0.2 | 10 | 80 | 17 | 14 | 0.14 |
| 420500031910 | 0.3 | 14 | 100 | 23 | 18 | 0.34 |
| 420500051910 | 0.5 | 16 | 130 | 32 | 22 | 0.56 |
| 420500081910 | 0.75 | 18 | 160 | 42 | 27 | 0.9 |
| 420500101910 | 1 | 20 | 180 | 48 | 37 | 1.2 |
| 420500131910 | 1.25 | 22 | 200 | 51 | 38 | 1.5 |
| 420500151910 | 1.5 | 26 | 220 | 55 | 50 | 2.3 |
| 420500201910 | 2 | 32 | 260 | 70 | 56 | 4.2 |
| 420500301910 | 3 | 36 | 320 | 84 | 65 | 6.4 |
| 420500401910 | 4 | 40 | 360 | 103 | 76 | 9 |
| 420500501910 | 5 | 45 | 400 | 110 | 76 | 13 |

Blueprint

