

## S Hook With Safety Latches On Both Sides 1730



### Product information

High quality S hook equipped with safety latches on both sides.

**Marking:** According to standard, CE-marked, Manufacturer sign, WLL, Date of Production MM/YY

**Temperature range:** -40°C up to +200°C

**Standard:** DIN EN 683-2

**Safety factor:** 4:1

**Grade:** 8

<b>Part Code</b>	<b>WLL ton</b>	<b>A mm</b>	<b>B mm</b>	<b>C mm</b>	<b>D mm</b>	<b>Weight kg</b>
420500011930	0.05	6	115	23	15	0.08
420500011931	0.1	8	115	23	15	0.1
420500021930	0.15	10	115	19	16	0.22
420500031930	0.25	12	153	31	23	0.42
420500041930	0.35	14	190	42	23	0.6
420500051930	0.5	16	230	55	36	1
420500081930	0.75	20	267	68	41	1.7
420500101930	1	22	305	81	50	2.2
420500131930	1.3	26	331	91	52	3.5
420500151930	1.5	28	380	105	70	4.5
420500201930	2	32	407	117	80	6.5
420500241930	2.4	36	430	130	80	8
420500281930	2.8	38	460	140	86	9.8
420500321930	3.2	40	500	149	96	11

# Blueprint

