

## Double Swivel Shackle Codipro OS DSS UP



### Product information

The universal swivel offshore shackle OS.DSS is a double swivel ring. It is designed for rotations under load. Its double swivel ensures perfect alignment with the sling. The lifting ring can swivel 180° but has a rotating range of 360°. DSS offshore lifting rings have a safety factor of 4 and 5, which means that their breaking load is four or five times greater than the capacity indicated in the technical sheet.

**Material:** High tensile steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +200°C

**Finish:** Lamellar coating

**Standard:** EN 1677-1

**Safety factor:** 5:1

Part Code	WLL ton	Thread mm	Torque Nm	L1 mm	S mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
4215OSDSSM24UP	4.5	M 24	160	36	19	61	31	70	98	73	149	33	5.4
4215OSDSSM30UP	7.7	M 30	250	45	19	61	31	70	98	73	149	33	5.5
4215OSDSSM36UP	11	M 36	320	54	19	61	31	70	98	73	149	33	5.5
4215OSDSSM42UP	13	M 42	400	63	19	61	31	70	98	73	149	33	5.8

# Blueprint

