

Double Swivel Ring Codipro OS DSR UP



Product information

The OS DSR UP offshore lifting ring is a double swivel ring. It is specially designed for simultaneously lifting and rotating loads. Its double swivel action ensures perfect alignment with the sling. The ring swivels 180° but has a rotating range of 360°. All DSR offshore lifting rings models have a safety factor of 4 and 5, which means that their breaking load is four or five times greater than the capacity indicated in the technical sheet.

Material: High tensile steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +200°C

Finish: Lamellar coating

Standard: EN 1677-1

Safety factor: 5:1

Part Code	WLL ton	Thread mm	Torque Nm	L1 mm	S1 mm	S2 mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg
4215OSDSRM10UP	0.7	M 10	10	18	8	16	33	30	30	38	27	14	53	9.5	0.3
4215OSDSRM12UP	1.05	M 12	15	21	8	16	33	30	30	38	27	14	53	9.5	0.3
4215OSDSRM16UP	2	M 16	50	27	8	20	45	40	45	53	38	17	76	13	0.9
4215OSDSRM203t2UP	2.9	M 20	100	25	14	24	62	55	60	83	55	25	115	19	2.6
4215OSDSRM24UP	4.4	M 24	160	36	14	24	62	55	60	83	55	25	115	19	2.6
4215OSDSRM306t3UP	6	M 30	250	45	14	24	62	55	60	83	55	25	115	19	2.7

Blueprint

