



## Wire Rope Snatch Block EH

### Product information

The single-sheave pulleys from the EH range are primarily intended for temporary lifting or cable traction installations, requiring quick setup and/or removal of the pulley. They can be anchored to a fixed or mobile point that has the necessary resistance to the applicable force.

The ease of setup and removal of these pulleys, along with the availability of a becket, make them suitable accessories for reeving and changing the direction of wire ropes.

The pulleys are equipped with a swivel hook that ensures proper orientation of the pulley in relation to the wire rope.

Wire rope snatch block fulfill the Machinery Directive 2006/42/EC.

**Marking:** CE-marked

**Finish:** Zinc-plated and dichromated

**Warning:** Never use for personnel lifting!

Part Code	Code	Rope Ø range mm	WLL ton	A mm	B mm	D mm	G mm	H mm	I mm	J mm	K mm	L mm	M mm	N mm	O mm	P mm	F mm	E mm	C mm	Weight kg
424100100760	E303H	8-9	1	33	43	24	225	386	355	106	38	50	37	32	13	8	80	100	8-9	3
424100100765	E305H	8-9	1	36	16	/	235	379	365	106	38	50	56	32	13	8	80	100	8-9	3
424100200760	E313H	10-12	2	41	59	30	315	541	482	170	58	77	56	40	17.5	16	132	160	10-12	7
424100240760	E460H	7.5-8.3	2.4	41	59	30	315	541	482	170	58	77	56	40	17.5	16	132	160	7.5-8.3	7
424100320760	E323H	13-15	3.2	49	60	38	369	631	562	210	80	94	53	40	17.5	16	160	200	13-15	15.5
424100480760	E470H	10-11.5	4.8	49	60	38	369	631	562	210	80	94	53	40	17.5	16	160	200	10-11.5	15.5
424100500760	E490H	13-15	5	49	60	38	368	646	567	210	80	94	69	60	25	20	160	200	13-15	17
424100500765	E333H	16-18	5	49	60	38	405	719	640	260	88	94	62	60	25	20	210	250	16-18	20.2
424100640760	E480H	14-16.3	6.4	68	80	48	510	896	794	343	92	110	75	70	30	25	275	336	14-16.3	34
424100800760	E347H	21-23	8	68	80	48	510	896	794	343	92	110	75	70	30	25	275	336	21-23	34

# Blueprint

