

## Flat webbing sling

### Product information



**General:** Flat webbing sling with simple eye – B type – Category 1

Identification : flat webbing sling in woven webbing

Type : Double ply (B type)

Configuration : Flexible sling consisting of a single element in sewn webbing

Endings : Simple eyes, category 1.

Traceability : High resisting blue pvc label sewn on the sling.

Instructions of use : Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. **DO NOT USE DAMAGED SLINGS.**

Storage : Store in a cool, dry and protected from sunlight area.

Maintenance : Never dry sling near a fire or any source of heat.

**Design:** Textile sleeve, 100% polyester, sewn around each eye to reinforce and protect its inner surface

**Stretch with working Load:** for textile slings

**Length Tolerance:** A

**Material:** 100% polyester multifilament fibres of high tenacity

**Marking:** According to standard, Manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

**Temperature range:** From -40°C to +100°C.

**Standard:** EN 1492-1

Part code

WLL  
ton

---

341100050100130	0.5
341100050150130	0.5
341100050200130	0.5
341100050250130	0.5
341100050300130	0.5
341100050400130	0.5
341100050500130	0.5
341100050600130	0.5
341100050700130	0.5
341100050800130	0.5
341100050900130	0.5
341100051000130	0.5
341100100100130	1
341100100150130	1
341100100200130	1
341100100250130	1
341100100300130	1
341100100400130	1
341100100500130	1
341100100600130	1
341100100700130	1
341100100800130	1
341100100900130	1

341100101000130	1
341100150100130	1.5
341100150150130	1.5
341100150200130	1.5
341100150250130	1.5
341100150300130	1.5
341100150400130	1.5
341100150500130	1.5
341100150600130	1.5
341100150700130	1.5
341100150800130	1.5
341100150900130	1.5
341100151000130	1.5
341100200100130	2
341100200150130	2
341100200200130	2
341100200250130	2
341100200300130	2
341100200400130	2
341100200500130	2
341100200600130	2
341100200700130	2
341100200800130	2

341100200900130	2
341100201000130	2
341100250100130	2.5
341100250150130	2.5
341100250200130	2.5
341100250250130	2.5
341100250300130	2.5
341100250400130	2.5
341100250500130	2.5
341100250600130	2.5
341100250700130	2.5
341100250800130	2.5
341100250900130	2.5
341100251000130	2.5
341100300100130	3
341100300150130	3
341100300200130	3
341100300250130	3
341100300300130	3
341100300400130	3
341100300500130	3
341100300600130	3
341100300700130	3

341100300800130	3
341100300900130	3
341100301000130	3
341100400100130	4
341100400150130	4
341100400200130	4
341100400250130	4
341100400300130	4
341100400400130	4
341100400500130	4
341100400600130	4
341100400700130	4
341100400800130	4
341100400900130	4
341100401000130	4
341100500100130	5
341100500150130	5
341100500200130	5
341100500250130	5
341100500300130	5
341100500400130	5
341100500500130	5
341100500600130	5

341100500700130	5
341100500800130	5
341100500900130	5
341100501000130	5
341100600100130	6
341100600150130	6
341100600200130	6
341100600250130	6
341100600300130	6
341100600400130	6
341100600500130	6
341100600600130	6
341100600700130	6
341100600800130	6
341100600900130	6
341100601000130	6
341100800100130	8
341100800150130	8
341100800200130	8
341100800250130	8
341100800300130	8
341100800400130	8
341100800500130	8

341100800600130	8
341100800700130	8
341100800800130	8
341100800900130	8
341100801000130	8
341101000100130	10
341101000150130	10
341101000200130	10
341101000250130	10
341101000300130	10
341101000400130	10
341101000500130	10
341101000600130	10
341101000700130	10
341101000800130	10
341101000900130	10
341101001000130	10

## Blueprint

