

## Flat webbing sling

### Product information



**General:** Flat webbing sling with simple eye – B type – Category 1

Identification : flat webbing sling in woven webbing

Type : Double ply (B type)

Configuration : Flexible sling consisting of a single element in sewn webbing

Endings : Simple eyes, category 1.

Traceability : High resisting blue pvc label sewn on the sling.

Instructions of use : Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. **DO NOT USE DAMAGED SLINGS.**

Storage : Store in a cool, dry and protected from sunlight area.

Maintenance : Never dry sling near a fire or any source of heat.

**Design:** Textile sleeve, 100% polyester, sewn around each eye to reinforce and protect its inner surface

**Stretch with working Load:** for textile slings

**Length Tolerance:** A

**Material:** 100% polyester multifilament fibres of high tenacity

**Marking:** According to standard, Manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

**Temperature range:** From -40°C to +100°C.

**Standard:** EN 1492-1

Part Code	WLL ton
341100050100130	0.5
341100100100130	1
341100150100130	1.5
341100200100130	2
341100250100130	2.5
341100300100130	3
341100400100130	4
341100500100130	5
341100600100130	6
341100800100130	8
341101000100130	10

## Blueprint

