

Flat webbing sling – B type – Category 4

Product information



General: Flat webbing sling – B type – Category 4

Type : Double ply (B type)

Configuration : Flexible sling consisting of a single element in sewn webbing

Endings : 2 triangular male rings made of steel, category 4.

Traceability : High resisting blue pvc label sewn on the sling.

Label informations : manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

Instructions of use : Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. **DO NOT USE DAMAGED SLINGS.**

Storage : Store in a cool, dry and protected from sunlight area.

Maintenance : Never dry sling near a fire or any source of heat.

Design: Flat webbing sling in woven webbingTextile sleeve, 100% polyester, sewn at the two endings to reinforce an protect the eyes

Stretch with working Load: for textile slings

Material: 100% polyester multifilament fibres of high tenacity

Marking: According to standard, A

Temperature range: From -40°C to +100°C.

Standard: EN 1492-1

Part Code	WLL ton
341100100100150	1
341100150100150	1.5
341100200100150	2
341100250100150	2.5
341100300100150	3
341100400100150	4
341100500100150	5
341100600100150	6
341100800100150	8
341101000100150	10

Technical data

New Table

Male buckle for flat webbing sling Cat. 4										
WLL (tons)	1	1,5	2	2,5	3	4	5	6	8	10
Ø (mm)	12	14	16	18	20	23	25	28	32	35
Webbing width (mm)	30	50	60	75	90	120	150	180	240	300
D (mm)	30	40	82	32	40	45	55	55	60	75
E (mm)	72	86	104	127	144	180	220	260	340	400
H (mm)	64	80	100	98	119	132	185	180	202	250

Blueprint

