

## Flat webbing sling – B type – Category 4

### Product information



**General:** Flat webbing sling – B type – Category 4

**Type:** Double ply (B type)

**Configuration:** Flexible sling consisting of a single element in sewn webbing

**Endings:** 2 triangular male rings made of steel, category 4.

**Traceability:** High resisting blue pvc label sewn on the sling.

**Label informations:** manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

**Instructions of use:** Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings.

**DO NOT USE DAMAGED SLINGS.**

**Storage:** Store in a cool, dry and protected from sunlight area.

**Maintenance:** Never dry sling near a fire or any source of heat.

**Design:** Flat webbing sling in woven webbingTextile sleeve, 100% polyester, sewn at the two endings to reinforce an protect the eyes

**Stretch with working Load:** for textile slings

**Material:** 100% polyester multifilament fibres of high tenacity

**Marking:** According to standard, A

**Temperature range:** From -40°C to +100°C.

**Standard:** EN 1492-1

Part Code

WLL  
ton

341100100100150

1

341100100150150	1
341100100200150	1
341100100250150	1
341100100300150	1
341100100400150	1
341100100500150	1
341100100600150	1
341100100700150	1
341100100800150	1
341100100900150	1
341100101000150	1
341100150100150	1.5
341100150150150	1.5
341100150200150	1.5
341100150250150	1.5
341100150300150	1.5
341100150400150	1.5
341100150500150	1.5
341100150600150	1.5
341100150700150	1.5
341100150800150	1.5
341100150900150	1.5
341100151000150	1.5

341100200100150	2
341100200150150	2
341100200200150	2
341100200250150	2
341100200300150	2
341100200400150	2
341100200500150	2
341100200600150	2
341100200700150	2
341100200800150	2
341100200900150	2
341100201000150	2
341100250100150	2.5
341100250150150	2.5
341100250200150	2.5
341100250250150	2.5
341100250300150	2.5
341100250400150	2.5
341100250500150	2.5
341100250600150	2.5
341100250700150	2.5
341100250800150	2.5
341100250900150	2.5

341100251000150	2.5
341100300100150	3
341100300150150	3
341100300200150	3
341100300250150	3
341100300300150	3
341100300400150	3
341100300500150	3
341100300600150	3
341100300700150	3
341100300800150	3
341100300900150	3
341100301000150	3
341100400100150	4
341100400150150	4
341100400200150	4
341100400250150	4
341100400300150	4
341100400400150	4
341100400500150	4
341100400600150	4
341100400700150	4
341100400800150	4

341100400900150	4
341100401000150	4
341100500100150	5
341100500150150	5
341100500200150	5
341100500250150	5
341100500300150	5
341100500400150	5
341100500500150	5
341100500600150	5
341100500700150	5
341100500800150	5
341100500900150	5
341100501000150	5
341100600100150	6
341100600150150	6
341100600200150	6
341100600250150	6
341100600300150	6
341100600400150	6
341100600500150	6
341100600600150	6
341100600700150	6

341100600800150	6
341100600900150	6
341100601000150	6
341100800100150	8
341100800150150	8
341100800200150	8
341100800250150	8
341100800300150	8
341100800400150	8
341100800500150	8
341100800600150	8
341100800700150	8
341100800800150	8
341100800900150	8
341100801000150	8
341101000100150	10
341101000150150	10
341101000200150	10
341101000250150	10
341101000300150	10
341101000400150	10
341101000500150	10
341101000600150	10

341101000700150	10
341101000800150	10
341101000900150	10
341101001000150	10

## Technical data

### New Table

Male buckle for flat webbing sling Cat. 4										
WLL (tons)	1	1,5	2	2,5	3	4	5	6	8	10
Ø (mm)	12	14	16	18	20	23	25	28	32	35
Webbing width (mm)	30	50	60	75	90	120	150	180	240	300
D (mm)	30	40	82	32	40	45	55	55	60	75
E (mm)	72	86	104	127	144	180	220	260	340	400
H (mm)	64	80	100	98	119	132	185	180	202	250

# Blueprint

