

Flat webbing – B type – Category 6

Product information



General: Identification : flat webbing sling in woven webbing

Type : Double ply (B type)

Configuration : Flexible sling consisting of a single element in sewn webbing

Endings : 2 torch cut male rings, category 6.

Traceability : High resisting blue pvc label sewn on the sling.

Instructions of use : Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. **DO NOT USE DAMAGED SLINGS.**

Storage : Store in a cool, dry and protected from sunlight area.

Maintenance : Never dry sling near a fire or any source of heat.

Design: Textile sleeve, 100% polyester, sewn at the two endings to reinforce and protect the eyes

Material: 100% polyester multifilament fibers of high tenacity

Marking: According to standard, Manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

Temperature range: From -40°C to +100°C.

Standard: EN 1492-1

Part Code

**WLL
ton**

341100400100170

4

341100400150170	4
341100400200170	4
341100400250170	4
341100400300170	4
341100400400170	4
341100400500170	4
341100400600170	4
341100400700170	4
341100400800170	4
341100400900170	4
341100401000170	4
341100500100170	5
341100500150170	5
341100500200170	5
341100500250170	5
341100500300170	5
341100500400170	5
341100500500170	5
341100500600170	5
341100500700170	5
341100500800170	5
341100500900170	5
341100501000170	5

341100600100170	6
341100600150170	6
341100600200170	6
341100600250170	6
341100600300170	6
341100600400170	6
341100600500170	6
341100600600170	6
341100600700170	6
341100600800170	6
341100600900170	6
341100601000170	6
341100800100170	8
341100800150170	8
341100800200170	8
341100800250170	8
341100800300170	8
341100800400170	8
341100800500170	8
341100800600170	8
341100800700170	8
341100800800170	8
341100800900170	8

341100801000170	8
341101000100170	10
341101000150170	10
341101000200170	10
341101000250170	10
341101000300170	10
341101000400170	10
341101000500170	10
341101000600170	10
341101000700170	10
341101000800170	10
341101000900170	10
341101001000170	10

Technical data

Male buckle for flat webbing sling Cat. 6					
WLL (tons)	4	5	6	8	10
A (mm)	85	85	105	114	107
B (mm)	110	110	120	145	141
C (mm)	29	27	30	44	48
D (mm)	137	158	198	252	305
E (mm)	18	20	20	20	25
F (mm)	178	198	258	328	390
G (mm)	148	155	170	210	212

Blueprint

