

DRAKO 250T

Product information



- 8-strand steel wire rope with steel core
- very low D/d ratio of up to 8 mm in diameter
- required drive torque is greatly reduced
- cost saving drives possible
- space saving in indirect hydraulic elevators thanks to very small pulley


Features: This rope is successfully used in diameters up to 13mm as a governor rope.

Rope construction: 8x19W-IWRC

Marking: According to standard

Standard: EN 12385-5

Elevator



| Part Code | Rope Diameter, mm | Tensile strength N/mm ² | Finish | Rope lay. | Min. Breaking force, kN | Steel area mm ² | Lubrication | Weight kg/100m |
|-----------------|-------------------|------------------------------------|------------|-----------|-------------------------|----------------------------|------------------|----------------|
| 106100604050269 | 6 | 1,770 | Bright | sZ | 26.8 | 17.1 | SupplierStandard | 16.4 |
| 106100654050269 | 6.5 | 1,770 | Bright | sZ | 31.5 | 20.7 | SupplierStandard | 17.9 |
| 106100804020269 | 8 | 1,570 | Bright | sZ | 43.3 | 30.9 | SupplierStandard | 27.3 |
| 106100904020269 | 9 | 1,570 | Bright | sZ | 54.8 | 38.6 | SupplierStandard | 34.3 |
| 106101004020269 | 10 | 1,570 | Bright | sZ | 67.7 | 49.2 | SupplierStandard | 42.3 |
| 106101003020269 | 10 | 1,570 | Bright | zS | 67.7 | 49.2 | SupplierStandard | 42.3 |
| 106101004220269 | 10 | 1,570 | Galvanized | sZ | 67.7 | 49.2 | SupplierStandard | 42.3 |
| 106101004050269 | 10 | 1,770 | Bright | sZ | 72.7 | 49.2 | SupplierStandard | 42.3 |
| 106101104020269 | 11 | 1,570 | Bright | sZ | 81.9 | 60.1 | SupplierStandard | 51.2 |
| 106101204020269 | 12 | 1,570 | Bright | sZ | 97.4 | 69.6 | SupplierStandard | 61 |
| 106101304020269 | 13 | 1,570 | Bright | sZ | 114 | 83.9 | SupplierStandard | 71.5 |
| 106101404020269 | 14 | 1,570 | Bright | sZ | 133 | 96 | SupplierStandard | 82.9 |