

DRAKO 250T

Product information



- 8-strand steel wire rope with steel core
- very low D/d ratio of up to 8 mm in diameter
- required drive torque is greatly reduced
- cost saving drives possible
- space saving in indirect hydraulic elevators thanks to very small pulley


Features: This rope is successfully used in diameters up to 13mm as a governor rope.

Rope construction: 8x19W-IWRC

Marking: According to standard

Standard: EN 12385-5

Elevator



Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force, kN	Finish	Weight kg/100m
106100604050269	6	1,770	17.1	26.8	Bright	16.4
106100654050269	6.5	1,770	20.7	31.5	Bright	17.9
106100804020269	8	1,570	30.9	43.3	Bright	27.3
106100904020269	9	1,570	38.6	54.8	Bright	34.3
106101004020269	10	1,570	49.2	67.7	Bright	42.3
106101003020269	10	1,570	49.2	67.7	Bright	42.3
106101004220269	10	1,570	49.2	67.7	Galvanized	42.3
106101004050269	10	1,770	49.2	72.7	Bright	42.3
106101104020269	11	1,570	60.1	81.9	Bright	51.2
106101204020269	12	1,570	69.6	97.4	Bright	61
106101304020269	13	1,570	83.9	114	Bright	71.5
106101404020269	14	1,570	96	133	Bright	82.9