

## DRAKO 250T

### Product information



- 8-strand steel wire rope with steel core
- very low D/d ratio of up to 8 mm in diameter
- required drive torque is greatly reduced
- cost saving drives possible
- space saving in indirect hydraulic elevators thanks to very small pulley


**Features:** This rope is successfully used in diameters up to 13mm as a governor rope.

**Rope construction:** 8x19W-IWRC

**Marking:** According to standard

**Standard:** EN 12385-5

Elevator



Part Code	Rope Diameter, mm	Steel area mm <sup>2</sup>	Min. Breaking force kN. 1770 N/mm <sup>2</sup>	Min. Breaking force kN. 1570 N/mm <sup>2</sup>	Finish	Weight kg/100m
106100604050269	6	17.1	26.8	-	Bright	16.4
106100654050269	6.5	20.7	31.5	-	Bright	17.9
106100804020269	8	30.9	-	43.3	Bright	27.3
106100904020269	9	38.6	-	54.8	Bright	34.3
106101004020269	10	49.2	72.7	67.7	Bright	42.3
106101104020269	11	60.1	-	81.9	Bright	51.2
106101204020269	12	69.6	-	97.4	Bright	61
106101304020269	13	83.9	-	114	Bright	71.5
106101404020269	14	96	-	133	Bright	82.9