



## Double Swivel Ring Codipro DSR UP

### Product information

The double swivel ring DSR UP has been especially designed to guarantee liftings under load. Its double articulation allows it to line up perfectly with the sling.

#### Features:

- Swiveling under load
- Usable for any kind of lifting operation
- Two ways of tightening:- Allen key or Torque wrench(also for external hex)
- The tightening torque is stamped on all lifting rings in the GRADUP range.

**Material:** High tensile steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +200°C

**Standard:** EN 1677-1  
*except grade/WLL*

**Safety factor:** 5:1

| Part Code       | WLL ton | Thread      | Torque Nm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | L1 mm | S1 mm | S2 mm | Weight kg | Delivery time |
|-----------------|---------|-------------|-----------|------|------|------|------|------|------|------|------|-------|-------|-------|-----------|---------------|
| 4215DSRM5UP     | 0.07    | M5 (x0.8)   | 3         | 33   | 30   | 30   | 38   | 27   | 14   | 53   | 9.5  | 15    | 8     | 16    | 0.3       | -             |
| 4215DSRM6UP     | 0.15    | M6 (x1)     | 4         | 33   | 30   | 30   | 38   | 27   | 14   | 53   | 9.5  | 15    | 8     | 16    | 0.3       | -             |
| 4215DSRM8UP     | 0.4     | M8 (x1.25)  | 6         | 33   | 30   | 30   | 38   | 27   | 14   | 53   | 9.5  | 15    | 8     | 16    | 0.3       | 2             |
| 4215DSRM10UP    | 0.7     | M10 (x1.50) | 10        | 33   | 30   | 30   | 38   | 27   | 14   | 53   | 9.5  | 18    | 8     | 16    | 0.3       | 2             |
| 4215DSRM12UP    | 1.05    | M12 (x1.75) | 15        | 33   | 30   | 30   | 38   | 27   | 14   | 53   | 9.5  | 21    | 8     | 16    | 0.3       | 2             |
| 4215DSRM14UP    | 1.4     | M14 (x2)    | 30        | 45   | 40   | 45   | 53   | 38   | 17   | 76   | 13   | 23    | 8     | 20    | 0.9       | 2             |
| 4215DSRM16UP    | 2       | M16 (x2)    | 50        | 45   | 40   | 45   | 53   | 38   | 17   | 76   | 13   | 27    | 8     | 20    | 0.9       | 2             |
| 4215DSRM18UP    | 2.3     | M18 (x2.5)  | 70        | 45   | 40   | 45   | 53   | 38   | 17   | 76   | 13   | 27    | 8     | 20    | 0.9       | 2             |
| 4215DSRM202T5UP | 2.5     | M20 (x2.5)  | 100       | 45   | 40   | 45   | 53   | 38   | 17   | 76   | 13   | 30    | 8     | 20    | 0.9       | 2             |
| 4215DSRM203T2UP | 2.9     | M20 (x2.5)  | 100       | 62   | 55   | 60   | 83   | 55   | 25   | 115  | 19   | 25    | 14    | 24    | 2.6       | -             |
| 4215DSRM22UP    | 3.5     | M22 (x2.5)  | 120       | 62   | 55   | 60   | 83   | 55   | 25   | 115  | 19   | 33    | 14    | 24    | 2.6       | 2             |
| 4215DSRM24UP    | 4.4     | M24 (x3)    | 160       | 62   | 55   | 60   | 83   | 55   | 25   | 115  | 19   | 36    | 14    | 24    | 2.6       | 2             |
| 4215DSRM27UP    | 5.7     | M27 (x3)    | 200       | 62   | 55   | 60   | 83   | 55   | 25   | 115  | 19   | 40    | 14    | 24    | 2.7       | -             |
| 4215DSRM306T3UP | 6       | M30 (x3.5)  | 250       | 62   | 55   | 60   | 83   | 55   | 25   | 115  | 19   | 45    | 14    | 24    | 2.7       | -             |
| 4215DSRM308TUP  | 6.7     | M30 (x3.5)  | 250       | 80   | 77   | 78   | 98   | 71   | 26   | 141  | 28   | 45    | 14    | 30    | 5.4       | -             |
| 4215DSRM36UP    | 8       | M36 (x4)    | 320       | 80   | 77   | 78   | 98   | 71   | 26   | 141  | 28   | 54    | 14    | 30    | 5.4       | -             |
| 4215DSRM42UP    | 8.5     | M42 (x4,5)  | 400       | 80   | 77   | 78   | 98   | 71   | 26   | 141  | 28   | 63    | 14    | 30    | 5.5       | -             |

# Blueprint

