



Swivel Shackle Mega double Codipro DSS UP

Product information

The universal swivel shackle MEGA DSS is a double swivel ring. It is specially designed for simultaneously lifting and rotating very heavy loads. Its double swivel action ensures perfect alignment with the sling.

Features:

- Swiveling under load
- Usable for any kind of heavy lifting operation
- The tightening torque is stamped on all lifting rings in the GRADUP range.

Material: High tensile steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +200°C

Finish: Red painted

Standard: EN 1677-1

except grade/WLL

Safety factor: 5:1

| Part Code | WLL ton | Thread | Torque Nm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | L1 mm | S mm | Weight kg |
|--------------------|---------|------------|-----------|------|------|------|------|------|------|------|-------|------|-----------|
| 4215MEGADSSM64UP | 30 | M 64 (x6) | 600 | 127 | 64 | 140 | 186 | 143 | 278 | 69 | 100 | 36 | 42 |
| 4215MEGADSSM72UP | 35 | M 72 (x6) | 700 | 127 | 64 | 140 | 186 | 143 | 278 | 69 | 110 | 36 | 43 |
| 4215MEGADSSM72X4UP | 35 | M 72 (x4) | 700 | 127 | 64 | 140 | 186 | 143 | 278 | 69 | 110 | 36 | 43 |
| 4215MEGADSSM80UP | 40 | M 80 (x6) | 800 | 127 | 64 | 140 | 186 | 143 | 278 | 69 | 120 | 36 | 44.5 |
| 4215MEGADSSM90UP | 50 | M 90 (x6) | 900 | 127 | 64 | 140 | 186 | 143 | 278 | 69 | 135 | 36 | 46.5 |
| 4215MEGADSSM100UP | 60 | M 100 (x6) | 1,000 | 127 | 64 | 140 | 186 | 143 | 278 | 69 | 150 | 36 | 49 |

Blueprint

