

## Screw Pin Chain Shackle Crosby G-210

### Product information

**Design:** Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

**Material:** Forged - Quenched and Tempered, with alloy pins.

**Marking:** According to standard, CE-marked

**Temperature range:** -40° C to 204° C

**Finish:** Hot Dip galvanized or self colored.

**Standard:** EN 13889, US. FED. SPEC. RR-C-271F

**Safety factor:** 6:1

**Grade:** 6



Part Code	WLL ton	Nominal Size (in.)	Tolerance +/- G	Tolerance +/- A	A mm	B mm	C mm	D mm	E mm	F mm	G mm	K mm	L mm	M mm	Weight kg	Delivery time
420100050030	0.5	1/4	1.5	1.5	11.9	7.87	6.35	6.35	24.6	15.5	22.4	40.4	4.83	35.1	0.05	-
420100750030	0.75	5/16	1.5	1.5	13.5	9.65	7.87	7.87	29.5	19.1	33	48.5	5.59	42.2	0.08	-
420100100030	1	3/8	3.3	1.5	16.8	11.2	9.65	9.65	35.8	23.1	31.8	58.5	6.4	51.5	0.13	-
420100150030	1.5	7/16	3.3	1.5	19.1	12.7	11.2	11.2	41.4	26.9	36.6	67.5	7.87	60.5	0.2	-
420100200030	2	1/2	3.3	1.5	20.6	16	12.7	12.7	46	30.2	41.4	77	9.65	68	0.27	-
420100330030	3.25	5/8	3.3	1.5	27	19.1	15.8	16	58.5	38.1	51	95	11.2	85	0.57	2
420100480030	4.75	3/4	6.35	1.5	31.8	22.4	20.6	19.1	70	46	60.5	115	12.7	101	1.19	-
420100650030	6.5	7/8	6.35	1.5	36.6	25.4	24.6	22.4	81	53	71.5	135	12.7	114	1.43	-
420100850030	8.5	1	6.35	1.5	42.9	28.7	25.4	25.4	93.5	60.5	81	151	14.2	129	2.15	-
420100950030	9.5	1 1/8	6.35	1.5	46	31.8	31.8	28.7	103	68.5	91	172	16	142	3.06	2
420101200030	12	1 1/4	6.35	3.3	51	35.1	35.1	31.8	115	76	100	191	17.5	156	4.11	-
420101350030	13.5	1 3/8	6.35	3.3	57	38.1	38.1	35.1	127	84	111	210	19.1	174	5.28	-
420101700030	17	1 1/2	6.35	3.3	60.5	41.4	41.2	38.1	137	92	122	230	20.6	187	7.23	-
420102500030	25	1 3/4	6.35	3.3	70	51	54	44.5	162	106	146	279	25.4	231	12.13	-
420103500030	35	2	6.35	3.3	82.5	57	51	51	184	122	171	312	30	263	19.19	-
420105500030	55	2 1/2	6.35	6.35	105	70	66.5	66.5	238	145	203	377	35.1	330	32.55	-

# Blueprint

