



Eye Hook Crosby S-1316, Type SHUR-LOC

Product information

- 25% stronger than Grade 80
- Individually Proof tested to 2-1/2 times the Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Eye style is designed with "Engineered Flat" to connect to S-1325 chain coupler.
- Suitable for use with Grade 100 and Grade 80 chain.
- The SHUR-LOCK hook, if properly installed and locked, can be used for personnel lifting applications and meets the intent of OSHA Rule 1926.1431 (g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.

Material: Forged Alloy steel - Quenched and Tempered.

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code	WLL ton	Chain mm	A mm	C mm	D mm	E mm	F mm	H mm	J mm	L mm	AA mm	Weight kg
402300150100	1.45	6	19.8	100	20.1	66	17	7.87	16	29.5	38.1	0.39
402300260100	2.6	7-8	27.4	135	27.9	88.9	22.1	9.91	20.6	37.6	51	0.82
402300400100	4	10	33	167	29.7	112	27.9	12.9	23.9	46.5	63.5	1.54
402300680100	6.8	13	41.9	209	42.4	139	32	17	29.5	56.4	76.2	2.72
402301030100	10.3	16	55.9	256	51.8	167	38.1	22.1	38.1	67.3	89	6.85
402301600100	16	18-20	64	274	56.4	197	51.1	22.1	51.6	89.4	-	8.62
402302000100	20	22	72.9	317	62.2	222	57.7	24.9	55.9	97.3	-	12.7
402302710100	27.1	26	80	371	81.5	251	62.5	32	68.1	104	-	22.5

Blueprint

