



## Clevis Hook Crosby S-1317

### Product information

- 25% stronger than Grade 80
- Individually Proof tested to 2-1/2 times the Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.

**Material:** Forged alloy steel, quenched and Tempered.

**Warning:** Not heat-treated

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | WLL ton | Chain mm | C mm | D mm | E mm | G mm | J mm | L mm | AA mm | Weight kg |
|--------------|---------|----------|------|------|------|------|------|------|-------|-----------|
| 402300150090 | 1.5     | 6        | 87.4 | 20.1 | 66   | 121  | 16   | 29   | 38.1  | 0.35      |
| 402300200090 | 2       | 7        | 114  | 27.9 | 89   | 159  | 20.6 | 35.1 | 51    | 0.82      |
| 402300260090 | 2.6     | 8        | 114  | 27.9 | 89   | 159  | 20.6 | 35.1 | 51    | 0.82      |
| 402300400090 | 4       | 10       | 140  | 29.7 | 112  | 192  | 24.1 | 46.5 | 63.5  | 1.66      |
| 402300680090 | 6.8     | 13       | 173  | 42.4 | 139  | 242  | 29.5 | 56.4 | 76.2  | 3.08      |
| 402301030090 | 10.3    | 16       | 209  | 51.8 | 167  | 295  | 38.1 | 67.3 | 89    | 5.4       |
| 402301600090 | 16      | 18-20    | 239  | 56.4 | 197  | 336  | 51.6 | 89.4 | -     | 6.8       |
| 402302000090 | 20      | 22       | 283  | 62.2 | 222  | 392  | 55.9 | 97.3 | -     | 12.7      |
| 402302710090 | 27.1    | 26       | 319  | 81.5 | 251  | 468  | 68.1 | 104  | -     | 22.5      |

## Blueprint

