



ROV Eye Hook Crosby L-320R

Product information

Features:

- QUIC-CHECK® deformation and angle indicators forged on the hook.
- Tip extension allows for easy handling.
- Sizes 3.2t through 31.5t utilize new integrated latch (S-4320) that meets the world-class standard for lifting.
- Heavy duty stamped latch interlocks with the hook tip.
- High cycle, long life spring.
- Pad eyes are provided on either side of hook as cable guides. The cable is passed through a hole drilled in the latch that assists in allowing the "remotely operated" cable to open latch.
- Cables and drilled latches are not provided by Crosby. They can be fitted by your local Authorized Crosby Dealer.

Material: Quenched and Tempered

Marking: Code

Finish: Painted with fluorescent yellow.

Safety factor: 4:1

Grade: 8

| Part Code | WLL ton | C mm | D mm | E mm | F mm | G mm | M mm | N mm | O mm | Q mm | R mm | AA** mm | Weight kg |
|--------------|------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|------------|--------------|
| 401300320160 | 3.2 | 119 | 101 | 25 | 41 | 29 | 24 | 15 | 28 | 32 | 6 | 50.8 | 1.01 |
| 401300540160 | 5.4 | 147 | 122 | 25 | 51 | 37 | 33 | 18 | 35 | 40 | 6 | 63.5 | 2.04 |
| 401300800160 | 8 | 187 | 159 | 35 | 64 | 46 | 42 | 23 | 41 | 51 | 10 | 76.2 | 3.92 |
| 401301150160 | 11.5 | 230 | 189 | 35 | 76 | 57 | 41 | 28 | 53 | 62 | 10 | 102 | 7.02 |
| 401301600160 | 16 | 256 | 211 | 35 | 83 | 66 | 49 | 32 | 58 | 72 | 10 | 102 | 10.1 |
| 401302200160 | 22 | 318 | 262 | 45 | 108 | 76 | 60 | 40 | 77 | 89 | 19 | 127 | 18.4 |
| 401303150160 | 31.5 | 357 | 346 | - | 127 | 92 | 76 | 44 | 86 | 89 | 19 | 165 | 28.1 |
| 401303700160 | 37 | 462 | 357 | - | 137 | 116 | 81 | 51 | 95 | 114 | 19 | 178 | 48.5 |
| 401304500160 | 45 | 511 | 392 | - | 152 | 129 | 82 | 55 | 125 | 125 | 19 | 203 | 62.1 |
| 401306000160 | 60 | 602 | 470 | - | 178 | 152 | 99 | 64 | 130 | 145 | 19 | 254 | 102 |

Blueprint

