

## Thimble G-414, Crosby - Extra heavy

### Product information

**General:**

The use of the G-414 extra heavy thimbles for your wire rope slings ensures a greater protection against wear of the wire rope and deformation of the wire rope eye.

**Features:**

- Longer service life.

**Material:** Steel

**Marking:** According to standard

**Finish:** Hot-dip galvanised

**Standard:** EN 13411-1



Part Code	Rope Ø range mm	Finish	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg/100pc
123100700230	6-7	Galvanized	55.5	41.4	38.1	22.4	11,2	7.1	1.5	5.85	3
123100800230	8	Galvanized	63.5	47.8	46	26.9	14,0	8.65	2.05	7.1	5.35
123101000230	9-10	Galvanized	73,0	54,0	54	28.7	16,8	10.4	2.8	8.65	9.8
123101200230	11-12	Galvanized	82.5	60.5	60.5	31.8	18.8	11.9	3.3	9.65	15.7
123101500230	13-15	Galvanized	92,0	70,0	70,0	38.1	23.4	13,5	3.55	10.4	23.1
123101600230	16	Galvanized	108	82.5	79.5	44.5	26,2	16.8	4.05	12.7	34.3
123102000230	18-20	Galvanized	127	95.5	96,5	51	33,0	19.8	5.6	16.8	72
123102200230	22	Galvanized	140	108	108	57	37,3	23.9	5.6	19.1	81
123102600230	24-26	Galvanized	156	114	125	63.5	44,5	26.9	6.35	22.4	142
123103200230	28-32	Galvanized	178	130	149	73	47,8	33.3	6.35	28.7	181
123103500230	32-35	Galvanized	230	165	173	89	57,2	36.6	9.65	28.7	402
123103800230	35-38	Galvanized	229	159	181	89	66,5	39.6	12.7	28.7	587
123104000230	40	Galvanized	286	203	207	102	76,2	43.7	12.7	35.1	771
123104400230	44	Galvanized	310	229	216	114	77,7	46.7	12.7	33.3	805
123105200230	48-52	Galvanized	384	305	264	152	85,9	53,0	12.7	38.1	1,259
123105600230	56	Galvanized	435	356	302	178	98,6	60.5	16,0	41.4	1,792

# Blueprint

