



Chain Sling CSX-176 Grade 10

Product information

Design: Chain sling with master link on one end and clevis safety hook on the other end.
 ø 19 and 22 mm chain are fitted with an eye safety hook. Other combinations possible on demand.

Dimensions: Ø 6–22 mm (other dimensions on demand).

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code	WLL ton
240500600050050	1.4
240500600100050	1.4
240500600150050	1.4
240500600200050	1.4
240500600300050	1.4
240500600400050	1.4
240500600500050	1.4

240500600600050	1.4
240500600000050	1.4
240500700050050	1.9
240500700100050	1.9
240500700150050	1.9
240500700200050	1.9
240500700300050	1.9
240500700400050	1.9
240500700500050	1.9
240500700600050	1.9
240500700000050	1.9
240500800050050	2.5
240500800100050	2.5
240500800150050	2.5
240500800200050	2.5
240500800300050	2.5
240500800400050	2.5
240500800500050	2.5
240500800600050	2.5
240500800000050	2.5
240501000050050	4
240501000100050	4
240501000150050	4

240501000200050	4
240501000300050	4
240501000400050	4
240501000500050	4
240501000600050	4
240501000000050	4
240501300050050	6.7
240501300100050	6.7
240501300150050	6.7
240501300200050	6.7
240501300300050	6.7
240501300400050	6.7
240501300500050	6.7
240501300600050	6.7
240501300000050	6.7
240501600050050	10
240501600100050	10
240501600150050	10
240501600200050	10
240501600300050	10
240501600400050	10
240501600500050	10
240501600600050	10

240501600000050	10
240501900050050	14
240501900100050	14
240501900150050	14
240501900200050	14
240501900300050	14
240501900400050	14
240501900500050	14
240501900600050	14
240501900000050	14
240502200050050	19
240502200100050	19
240502200150050	19
240502200200050	19
240502200300050	19
240502200400050	19
240502200500050	19
240502200600050	19
240502200000050	19